



GE Industrial Systems


[GE Home](#) |
 [GE Industrial Home](#) |
 [Products](#) |
 [Markets](#) |
 [Services](#) |
 [Solutions](#) |
 [Support](#) |
 [About Us](#) |
 [Feedback](#)
[Quick Search](#) |
 [Where To Buy](#) |
 [Contact Us](#)

[← Back](#)

PRODUCT DETAILS

Product Number: H120

Model Number: 5KH32FN3123



FEATURES:

Ball bearings
 Reversible rotation
 Selected Energy Saver (E\$) designs available

APPLICATIONS: Designed for applications having hard or heavy duty starting loads in dirty or dusty areas, like industrial machinery and pumps, conveyors, and farm equipment.

Distributor List Price: \$161.00

Product Resources Select One

-Select a resource & click GO-

Product Specifications

Category	Farm Duty, General Purpose Motors, OEM Replacement Motors, Pump Motors
Application	General Purpose Motors, OEM Replacement Motors
Phase	Single Phase
Motor Type	Base Mounted - Capacitor Start - Totally Enclosed Fan Cooled - Foot Mounted
Horsepower	1/4
Speeds	1
RPM	1725
Volts	115
Hertz	60
Service factor	1.0
Full load amps	5.1
Frame Size	48
Enclosure	TEFC
Bearings	Ball
Rotation	CCW/CW
Thermal protection	None
Mounting type	WB
C_dim	9.92
Weight	14
Notes	39
OEM name	Greenheck Fan



GE Industrial Systems


[GE Home](#) |
 [GE Industrial Home](#) |
 [Products](#) |
 [Markets](#) |
 [Services](#) |
 [Solutions](#) |
 [Support](#) |
 [About Us](#) |
 [Feedback](#)
[Quick Search](#) |
 [Where To Buy](#) |
 [Contact Us](#)

[Back](#)

PRODUCT DETAILS

Product Number: H164

Model Number: 5KH32JN3128



FEATURES:

- Sleeve or ball bearings
- Reversible rotation
- Optional extended clamp bolts
- Moderate starting torque

APPLICATIONS: Designed for applications having moderate starting loads, like commercial fans and blowers, direct and belt drive air handlers, and exhaust fans.

Distributor List Price: \$148.00

Product Resources Select One

-Select a resource & click GO-



Product Specifications

Category	Air Moving Motors
Application	Fan & Blower
Phase	Single Phase
Motor Type	Split Phase - Dripproof - Single Speed
Horsepower	1/3
Speeds	1
RPM	1725
Volts	115
Hertz	60
Service factor	1.35
Full load amps	6.2
Frame Size	48Z
Enclosure	DP
Bearings	Ball
Rotation	ECCW
Thermal protection	None
Mounting type	RBE
C_dim	9.3
Weight	15
Notes	8